

Bimanual System Disposable Irrigation Aspiration 20G, 21G







BSD 500

Bimanual System Disposable 21G consisting of:

- 1 Irrigation Handpiece with curved cannula, open end flushing 45° tip
- 1 Aspiration Handpiece with curved cannula, Asp. Port ø 0.35 mm rough tip





BSD 510

Bimanual System Disposable 21G consisting of:

- 1 Irrigation Handpiece with curved cannula, dual side ports ø 0.45~mm
- 1 Aspiration Handpiece with curved cannula, Asp. Port ø 0.35 mm rough tip





BSD 515

Bimanual System Disposable 21G consisting of:

- 1 Irrigation Handpiece with curved cannula, dual side ports ø 0.45 mm
- 1 Aspiration Handpiece with curved cannula, Asp. Port ø 0.35 mm smooth tip





BSD 560

Bimanual System Disposable 20G consisting of:

- 1 Irrigation Handpiece with curved cannula, dual side ports ø 0.65 mm
- 1 Aspiration Handpiece with curved cannula, Asp. Port ø 0.35 mm rough tip





BSD 565

Bimanual System Disposable 20G consisting of:

- 1 Irrigation Handpiece with curved cannula, dual side ports ø 0.65
- 1 Aspiration Handpiece with curved cannula, Asp. Port ø 0.35 mm smooth tip



Product Features:

Troduct reatures.	BSD 500	BSD 510	BSD 515	BSD 560	BSD 565
Single use / no risk of cross contamination	•	•	•	•	•
Lightweight, colour-coded Handpieces	•	•	•	•	•
Standard male/female Luer connector	•	•	•	•	•
Compatible with your Phaco or I/A System	•	•	•	•	•
Aspiration port Ø 0.35 mm, roughened tip	•	•		•	
Aspiration port ø 0.35 mm, smooth tip			•		•
Aspiration port Ø 0.30 mm, roughened tip					
Aspiration port ø 0.30 mm, smooth tip Irrigation front flushing 45°, inner lumen 0.6					
mm	•				
Irrigation dual side ports Ø 0.45 mm		•	•		
Irrigation dual side ports Ø 0.65 mm				•	•
Smooth bullet-shaped tip		•	•	•	•

Version 06/2015



Bimanual System Disposable Irrigation Aspiration 20G, 21G







BSD 500

Bimanual System Disposable 21G consisting of:

- 1 Irrigation Handpiece with curved cannula, open end flushing 45° tip
- 1 Aspiration Handpiece with curved cannula, Asp. Port ø 0.35 mm rough tip





BSD 510

Bimanual System Disposable 21G consisting of:

- 1 Irrigation Handpiece with curved cannula, dual side ports ø 0.45~mm
- 1 Aspiration Handpiece with curved cannula, Asp. Port ø 0.35 mm rough tip





BSD 515

Bimanual System Disposable 21G consisting of:

- 1 Irrigation Handpiece with curved cannula, dual side ports ø 0.45 mm
- 1 Aspiration Handpiece with curved cannula, Asp. Port ø 0.35 mm smooth tip





BSD 560

Bimanual System Disposable 20G consisting of:

- 1 Irrigation Handpiece with curved cannula, dual side ports ø 0.65 mm
- 1 Aspiration Handpiece with curved cannula, Asp. Port ø 0.35 mm rough tip





BSD 565

Bimanual System Disposable 20G consisting of:

- 1 Irrigation Handpiece with curved cannula, dual side ports ø 0.65
- 1 Aspiration Handpiece with curved cannula, Asp. Port ø 0.35 mm smooth tip



Product Features:

Troduct reatures.	BSD 500	BSD 510	BSD 515	BSD 560	BSD 565
Single use / no risk of cross contamination	•	•	•	•	•
Lightweight, colour-coded Handpieces	•	•	•	•	•
Standard male/female Luer connector	•	•	•	•	•
Compatible with your Phaco or I/A System	•	•	•	•	•
Aspiration port Ø 0.35 mm, roughened tip	•	•		•	
Aspiration port ø 0.35 mm, smooth tip			•		•
Aspiration port Ø 0.30 mm, roughened tip					
Aspiration port ø 0.30 mm, smooth tip Irrigation front flushing 45°, inner lumen 0.6					
mm	•				
Irrigation dual side ports Ø 0.45 mm		•	•		
Irrigation dual side ports Ø 0.65 mm				•	•
Smooth bullet-shaped tip		•	•	•	•

Version 06/2015